

Use the IZ's apikey (permissions: read/write Bibs, read Users) found in the IZ's Developer Network account under "My APIs"

URL: <https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/integration-profiles?>

```
+ apikey=xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
```

```
+ &type=REMOTE_STORAGE
```

Link (for GW PSB):

https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/integration-profiles?apikey=l8xxdd61599bea484b8d8b7d84a722da788e&type=REMOTE_STORAGE

Intermediate Result:

```
<integration_profiles total_record_count="1">
  <integration_profile
    link="https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/integration-profiles/10385500680004107">
      <id>10385500680004107</id>
      <code>SCF-RS</code>
      <name>Shared Collections Facility</name>
      <type desc="Remote Storage">REMOTE_STORAGE</type>
      <system desc="XML">XML</system>
      <ftp_connection desc="NZ-managed SFTP site for the Alma Remote Storage App">SFTP for SCF App</ftp_connection>
      <default>false</default>
      <description>IMPORTANT: Do not edit this profile without communicating with WRLC Central staff. If you save edits it will change the ID of the job to export requests that the Remote Storage App looks for in the Job Finish Webhook.</description>
      <parameters>
        <parameter>
          <action desc="" active="false">SWISSLOG_SYNQ</action>
          <name desc="">url</name>
        </parameter>
        <parameter>
          <action desc="" active="false">SWISSLOG_SYNQ</action>
          <name desc="">owner</name>
        </parameter>
      </parameters>
      ...
    </integration_profile>
  </integration_profiles>
```

The `<id>10385500680004107</id>` element is the `profile_id` used to get `request_job_id`.

URL: <https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/jobs?>

```
+ apikey=xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
```

[illegible]

Link (for GW PSB)

https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/jobs?apikey=l8xxdd61599bea484b8d8b7d84a722da788e&profile_id=10385500680004107

Result:

```
<jobs total_record_count="2">
  <job
    link="https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/jobs/S1567029063004107">
      <id>S15670290630004107</id>
      <name>Inventory Remote Storage Update - Shared Collections Facility</name>
      <description>Inventory Remote Storage Update - Shared Collections
        Facility</description>
      <type desc="Scheduled">SCHEDULED</type>
      <category desc="Repository">REPOSITORY</category>
      <schedule/>
      <creator>WRLCadmin</creator>
      <related_profile>10385500680004107</related_profile>
    </job>
    <job
      link="https://api-na.hosted.exlibrisgroup.com/almaws/v1/conf/jobs/S1567029062004107">
        <id>S15670290620004107</id>
        <name>Send Requests to Remote Storage</name>
        <description>Remote Storage - Export Requests</description>
        <type desc="Scheduled">SCHEDULED</type>
        <category desc="Fulfillment">FULFILLMENT</category>
        <schedule desc="Every 12 hours, starting at 24:00">EVERY_12_HOUR</schedule>
        <creator>WRLCadmin</creator>
        <next_run>2024-09-04T15:00:00Z</next_run>
        <related_profile>10385500680004107</related_profile>
      </job>
    </jobs>
  </jobs>
```

The `<id>S15670290630004107</id>` element has the value of the `request_job_id`.

This value is put into the `conf.json` file used by the SCFApp.

Note: If a change is made/saved to the Integration profile, the request_job_id will be changed. In this event, the new profile id and request_job_id will need to be found.